

DIGITUS USB-C™ Docking Station, 12-Port

DA-70888

EAN 4016032464747



12-Port USB-C Dock, grey, HDMI, VGA, 2x USB-C, 4x USB-A, RJ45, 1x 3.5mm, SD/MicroSD

The multifunctional DIGITUS® docking station has everything you need to create a fully equipped workplace. Via the HDMI® and VGA port, you can extend your desktop to 2 additional monitors or connect projectors / TV devices. In combination with your existing screen, this allows you to clone your desktop on up to 3 displays or extend on up to 2 displays (2 extended + 1 cloned). Additionally, the docking station is equipped with two USB-C™ ports, one of which features Power Delivery (PD). This allows you to charge your connected notebook / tablet while in use. Via the second USB-C™ port, you can connect additional USB-C™ devices. Four additional USB ports provide you with plenty of space to connect additional mobile devices, which can be charged while in use. Of course, other USB peripheral devices such as a mouse or keyboard can also be connected using the 4 USB ports (2 x USB 3.0 / 2 x USB 2.0). Two card readers for SD/TF cards and MicroSD cards are also integrated, as is a gigabit Ethernet port. This allows you to connect your notebook to the local network or Internet via the docking station using a network cable. The Desktop-Multi-Tool features are rounded off with a stereo audio jack. This allows you to use a microphone, speaker, or headset. With the multifunctional DIGITUS® docking station, you can extend your notebook, tablet or smartphone with just one USB-C™ port.

The DIGITUS® USB-C™ docking station extends your notebook or tablet by 12 additional connections

- 1 x HDMI® connection: 4K / 30 Hz (3840 x 2160p), 1080p / 60 Hz when using HDMI + VGA
- 1 x VGA connection: Full HD (1920 x 1080p, 60 Hz)
- 1 x USB-C™ plug: Connection with the host (notebook, tablet)
- 1 x USB-C™ connection: SuperSpeed, 5 Gbps
- 1 x USB-C™ connection: Power Delivery 3.0 (100 W max.)
- 2 x USB 3.0 connection: 5 Gbps, 4.5 W (5 V / 0.9 A)
- 2 x USB 2.0 connections: 480 Mbps, 4.5 W (5 V / 0.9 A)
- 1 x SD card reader: 480 Mbps

- 1 x MicroSD card reader: 480 Mbps
- 1 x Gigabit Ethernet interface: 10/100/1000 Mbps
- 1 x audio connection: 3.5 mm stereo (stereo-audio, microphone)
- Plug and Play - no driver or app installation required
- Operating systems: Windows 10/8/7 macOS® 9.X & 10.X, Linux, ChromeOS, Android, iOS®
- Operating temperature: -40°C ~ 80°C
- Connection cable length: 20 cm
- Housing: Zinc plating with silicone surface
- Dimensions: L 29.1 x W 7.6 x H 2.1 cm
- Weight: 535 g
- Color: Black
- Manufacturer's notice:
- Manufacturer's notice:
- Not all USB-C™ ports support all functions of the USB Type-C™ standard. Make sure that your notebook's USB-C™ port supports the DisplayPort Alternate Mode (DP Alt Mode) as well as USB Power Delivery (PD).
- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- Housing: Aluminum
- LAN connector (RJ45): yes
- USB-C Power Delivery: 100W
- Card reader: yes
- Number of audio ports: 1
- Number of display ports: 2
- Number of network ports: 1
- Number of USB A ports: 4
- Number of USB-C ports: 2
- Number of video ports: 2
- USB-C Products: yes
- Video connection ports: HDMI, VGA

Package contents

- USB-C™ Docking Station, 12-Port
- QIG

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 20 | 14.50 | 34.50 | 34.50 | 43.50 | 51,775.90 |
| Packaging Unit Inside | 1 | 0.73 | 33.00 | 12.50 | 4.30 | 1,773.75 |
| Packaging Unit Single | 1 | 0.73 | 33.00 | 12.40 | 4.30 | 1,759.56 |
| Net single without Packaging | 1 | 0.35 | 29.10 | 7.60 | 2.10 | 0.00 |

More images:

