# DIGITUS FTTX enclosure, empty for 4 x SC SX, LC DX couplers

**DN-931093**
**EAN 4016032466529**

**FTTX enclosure, empty for 4x SC SX,LC DX surface and DIN-rail mount**

The FTTX housing can hold up to 4 fiber optic cables and distribute them to 4 end devices with the matching couplings. Holds 4 x SC Simplex or 4 x LC Duplex couplings (without flange). The housing consists of a front panel, the housing with expandable splice cassette and a transparent plastic cover for additional protection of the spliced fiber optic cable. The box can be mounted on the wall or snapped onto a profile rail (DIN rail). Bring together fiber splices, terminations, storage and connections in a minimal space with the ultra-compact DIGITUS® FTTX.

**FTTX housing for fiber splices, terminations, storage and connections in a compact protective housing**

- Suitable for 4 ports: 4 x SC SX / 4 x LC DX (without flange)
- Integrated splice cassette
- Protection type: IP45
- Installation: Wall or profile rail (DIN rail)
- Suitable for single-mode and multi-mode fiber optic cables
- Operating temperature: -40°C ~ +85°C
- Housing material: PC + ABS
- Dimensions: 100 x 80 x 30 mm (LxWxH)
- Weight: 0.4 kg
- Color: Gray

**Package contents**

- FTTX Housing for 4 x SC SX / LC DX Couplings

| Logistics | | | | | | |
|---|---|---|---|---|---|---|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 100 | 10.50 | 49.00 | 23.50 | 41.00 | 47,211.50 |
| Packaging Unit Inside | 1 | 0.11 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.11 | 9.30 | 10.50 | 3.80 | 371.07 |
| Net single without Packaging | 1 | 0.09 | 8.40 | 9.50 | 2.60 | 0.00 |

**More images:**