

DIGITUS Safety Plug for Flush Mounting with 1 x USB Type-C™, 1 x USB A

DA-70615
EAN 4016032443223



Wall Outlet 1x Safety Outlet, 1x USB, 1x Type C 5 V 2.8 A, Input: AC 250V 50Hz, RAL 9003

Charge your smartphone at any socket! With the DIGITUS® safety plug socket you can even charge 2 smartphones at the same time. Charge one USB-C™ or USB A device with up to 14 W (5 V / 2.8 A). For example, with 2.8 A available charging current you can simultaneously charge your smartphone and tablet. Protect you and your family by the integrated shutters in the safety socket and inbuilt electronic short circuit and overload protection in the USB ports. Upgrade your existing electrical installations and enjoy being able to charge your USB devices at any time, directly from the socket.

1 x USB Type-C™ connection + 1 x USB A connection for charging smartphones or tablets

- Integrated shutters in the socket for increased protection against accidental contact

- 1 x USB Type-C™, 1 x USB A port,
- Output voltage: 5 VDC (USB)
- Output voltage: 250 VAC (safety plug socket)
- Mounting: Flush mount
- Total output current: max. 2.8 A (USB-C™ + USB A)
- Installation depth: 32 mm
- Safety: Secured with electronic short circuit and overload protection (USB)
- Intelligent parallel usage of all connections (USB up to 3.4 A)
- Color: Signal white RAL 9003

Package contents

- Safety plug for flush mounting with 1 x USB Type-C™, 1 x USB A port
- Installation instructions

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	50	7.80	48.00	35.00	20.50	34,440.00
Packaging Unit Inside	1	0.16	9.00	9.00	6.00	486.00
Packaging Unit Single	1	0.16	9.00	6.00	12.00	648.00
Net single without Packaging	1	0.10	8.00	4.00	8.00	0.00

More images:



